



AquaTrue

정밀도 : 13 arc · Minute
 Size : 60, 80, 120, 160 mm
 감속 비율 : 3:1~100:1
 토크 범위 : 최대 876Nm
 방수등급 : IP66 / IP67



XTrue

정밀도 : 13 arc · Minute
 Size : 40, 50, 60, 70, 80, 90, 120, 160mm
 감속 비율 : 3:1~100:1
 토크 범위 : 최대 876Nm



NemaTrue

정밀도 : 13 arc · Minute
 Size : 17, 23/63mm, 34/90mm, 42/115mm
 감속 비율 : 3:1~100:1
 직선형 (Right Angle Type) 가능 : Size 23, 34, 42



UltraTrue

정밀도 : 4 arc · Minute
 Size : 60, 75, 90, 100, 115, 140, 180, 220mm
 감속 비율 : 4:1~100:1
 직각형 (Right Angle Type) UTR Series 가능
 UTR Size : 60, 75, 90, 100, 115, 142, 140
 UTR 감속비 : 1:1~50:1



DuraTrue

정밀도 : 8 arc · Minute
 Size : 60, 90, 115, 142mm
 감속 비율 : 3:1~100:1 (고비율 가능)
 직각형 (Right Angle Type) 가능
 감속비 : 1:1~500:1



ValueTrue

정밀도 : 4 arc · Minute
 Size : 60, 75, 90, 100, 115, 180, 220mm
 비율 : 4:1~100:1
 직각형 (Right Angle Type) VTR Series 가능
 프레임 Size : 60, 75, 90, 100, 115, 140, 180



DuraTrue (Hollow/Dual Shaft)

중공형 (Hollow Shaft)
 양축형 (Dual Shaft) 가능
 정밀도 : 8 arc · Minute
 Size : 90, 115, 142mm
 감속비 : 1:1~500:1



EverTrue (Continuous Duty)

연속 부하용 (30,000시간 보장)
 정밀도 : 4 arc · Minute
 Size : 100, 140, 180mm
 감속비 : 4:1~100:1